

Thermoplastic Rubber | TPR



Features

- Non-marking Thermoplastic Rubber tread on polyolefin core
- 70 (±5) Durometer Shore (A)
- Recommended for clean environments
- Resists most solvents, oil, grease, and water
- Smooth rolling and quiet
- Light weight
- Temp Range: -45°F to +180°F

Options

Donut Tread (DPR)

Wheel Dia.	Tread Width	Part #
3	1-1/4	314DPR
3-1/2	1-1/4	3514DPR
4	1-1/4	414DPR
4	2	420DPR
5	1-1/4	514DPR
5	2	520DPR
6	1-1/4	614DPR
6	2	620DPR
8	2	820DPR

Wheel Dia.	Tread Width	Hub Length	Load Cap.	Part #	* Bearings Options			
					Plain Bore	Roller	Precision Ball	Flanged Ball
2	7/8	1	130	278TPR*	80	--	--	--
2-1/2	7/8	1	150	2578TPR*	80	--	--	--
3	7/8	1	150	378TPR*	80	--	--	--
3	1	1-1/8	160	310TPR*	81	--	31	--
3	1-1/4	1-9/16	210	314TPR*	91	--	34	--
3-1/2	1-1/4	1-9/16	250	3514TPR*	91	--	34	--
4	1	1-1/8	175	410TPR*	81	--	31	--
4	1-1/4	1-9/16	300	414TPR*	91	--	34	--
4	1-1/2	1-5/8	400	415TPR*	84	23	38	--
4	2	2-3/16	450	420TPR*	84	23	38	--
5	1	1-1/8	200	510TPR*	81	--	--	--
5	1-1/4	1-9/16	300	514TPR*	91	--	34	--
5	1-1/2	1-5/8	450	515TPR*	84	23	38	--
5	2	2-3/16	500	520TPR*	84	23	38	--
6	1-1/4	1-9/16	300	614TPR*	91	-	34	--
6	1-1/2	1-5/8	500	615TPR*	84	23	38	--
6	2	2-3/16	550	620TPR*	84	23	38	--
6	2-1/2	2-3/4	700	625TPR*	84, 86	23, 25	38, 39	--
6	3	3-1/4	800	630TPR*	86	25	39	--
8	1-1/2	1-5/8	550	815TPR*	84	23	38	45, 46
8	2	2-3/16	600	820TPR*	84	23	38	--
8	2-1/2	2-3/4	800	825TPR*	84, 86	23, 25	38, 39	--
8	3	3-1/4	900	830TPR*	86	25	39	--
10	1-1/2	1-5/8	900	1015TPR*	84	23	38	45, 46
10	2-1/2	2-3/4	1000	1025TPR*	84, 86	23, 25	38, 39	--
10	3	3-1/4	1300	1030TPR*	86	25	39	--
12	2-1/2	2-3/4	1400	1225TPR*	84, 86	23, 25	38, 39	--
12	3	3-1/4	1500	1230TPR*	86	25	39	--

Rubbers
Wheels

For more information: www.durastarcasters.com



1500 lbs
680 kg