

# Formula XS

High Tech Rubber | FX

## Features

- 65 (±5) Durometer Shore (A)
- Thermoplastic elastomer (non-marking) mechanically bonded to polyolefin
- Temp Range: -45°F to +180°F

## Applications

- Factory environments
- Institutional
- Food Service

## Options

Donut Tread | DFX

The EXTREME High Tek  
**PERFORMANCE  
FORMULA**

- Extreme performance and versatility
- Shock Absorbtion
- Flat-Spotting resistance under heavy loads
- Impact Resistance
- No corrosion in harsh environments

- Hot or Cold temperatures
- Inside or Outside applications
- Repels chemicals, acids, oils, water and more.
- Rejects metal shavings, gravel, and debris.
- Smooth rolling and quiet



Wheel Dia.	Tread Width	Hub Length	Load Cap.	Part #	* Bearings Options				
					Plain Bore	Annular Ball	Roller	Precision	Delrin
2-1/2	1-1/4	1-9/16	150	2514FX35X	--	--	--	35	--
3	1-1/4	1-5/8	300	314FX*	89	11	--	35	56
3-1/2	1-1/4	1-1/2	300	3514FX*	89	11	--	35	56
4	1-1/4	1-1/2	300	414FX*	89	11	--	35	56
4	1-1/2	1-5/8	400	415FX*	84	12	23	38	57
4	2	2-3/16	450	420FX*	84	12	23	38	57
5	1-1/4	1-1/2	325	514FX*	89	11	--	35	56
5	1-1/2	1-5/8	450	515FX*	84	12	23	38	57
5	2	2-3/16	500	520FX*	84	12	23	38	57
6	1-1/2	1-5/8	500	615FX*	84	12	23	38	57
6	2	2-3/16	600	620FX*	84	12	23	38	57
8	2	2-3/16	675	820FX*	84	12	23	38	57

About DuraStar Caster Mfg, Intl. – Everest Casters & Wheels LLC

For more than 25 years, DuraStar has been an international manufacturer of world-class casters, wheels, and related accessories. Headquartered in Taiwan, with factory holdings in China and a distribution branch in North America (Everest Casters), DuraStar is equipped with over 120,000 square feet of ultramodern production and warehouse space, as well as a progressive team of avant-garde engineers at your service. For more information, visit

