28 Series

350 lbs
160 kg

1¼ 3 4 5

The 28 Series was made for laboratory and medical equipment. Its impact and chemical resistance make it perfect for hazardous environments.

Light-Medium Duty Caster

Load Capacity
350 lbs
160 kg

Features

- Glass-filled nylon yoke construction for increased strength
- Highly impact absorbent
- Resists water chemicals solvents and oils
- Smooth precision ball bearing raceway
- Highly maneuverable and quiet

Industries and Applications

- Medical
- Electronics
- Laboratory

Size	Bolt Pattern	Attaching Bolt Dia.	**Plate
2-3/8 x 3-5/8	1-3/4 x 2-7/8 to 3	5/16	01

Size	Stem Type	**Stem
1/2-13 x 1	Threaded Stem	41
1/2-13 x 1-1/2	Threaded Stem	43
7/16 x 1-3/8	Grip Ring	72

Caster Type	Part #
Swivel	***CS***
Swivel/Total Lock Brake	***TL***
Swivel/Directional Lock Brake	***DL***

Wheel Dia.	Tread Width	Wheel Type	Load Cap.	OAH	Radius	Bearing	Swivel Part #
3	1-1/4	Thermoplastic Rubber	210	4-3/4	3-1/16	Precision	28***CS***314TPR31-**
3	1-1/4	FX Thermoplastic Rubber	225	4-3/4	3-1/16	Precision	28***CS***314FX31-**
3	1-1/4	Polyurethane | Polyolefin	250	4-3/4	3-1/16	Precision	28***CS***314PPU31-**
3	1-1/4	Duratough Polyurethane | Polyolefin	275	4-3/4	3-1/16	Precision	28***CS***314PTU31-**
4	1-1/4	Thermoplastic Rubber	250	5-7/16	3-3/8	Precision	28***CS***414TPR31-**
4	1-1/4	FX Thermoplastic Rubber	300	5-7/16	3-3/8	Precision	28***CS***414FX31-**
4	1-1/4	Polyurethane | Polyolefin	300	5-7/16	3-3/8	Precision	28***CS***414PPU31-**
4	1-1/4	Duratough Polyurethane | Polyolefin	325	5-7/16	3-3/8	Precision	28***CS***414PTU31-**
5	1-1/4	Thermoplastic Rubber	300	6-1/2	4-1/2	Precision	28***CS***514TPR31-**
5	1-1/4	FX Thermoplastic Rubber	315	6-1/2	4-1/2	Precision	28***CS***514FX31-**
5	1-1/4	Polyurethane | Polyolefin	325	6-1/2	4-1/2	Precision	28***CS***514PPU31-**
5	1-1/4	Duratough Polyurethane | Polyolefin	350	6-1/2	4-1/2	Precision	28***CS***514PTU31-**