

C47 Chrome Series

2
4
5
6
8



Professional Precision Yokes

Engineered with professionalism in mind, the Chrome 47 Series offers a maintenance free option that adds value through longevity.



Features

- Chrome plated for extended life
- Sealed precision raceway
- Maintenance-free
- Ultra ergonomic



Heavy Duty Caster

Load Capacity
2000 lbs
900 kg

Industries and Applications

Industrial
 Machinery/Fabrication
 Institutional
 Automotive
 Tow-Line



Size	Bolt Pattern	Attaching Bolt Dia.	**Plate
4 x 4-1/2	2-5/8 x 3-5/8 to 3 x 3	3/8	03

Caster Type	Part #
Swivel	CS
Rigid	CR
Swivel/Top Lock Brake	TS

Bearing Options	^ Part #
Roller	23
Q34 Precision Ball	38
1/2 I.D. Delrin	56
3/4 I.D. Delrin	57
6203 Precision Ball	63
6204 Precision Ball	64

Wheel Dia.	Tread Width	Wheel Type	Load Cap.	OAH	Radius	Swivel Part #	^ Bearing Options
4	2	Yoke Only	2000	5-5/8	3-1/8	C47 CS 420-**	23, 38, 56, 57
4	2	Elastic Rubber Nylon	400	5-5/8	3-1/8	C47 CS 420ERN^.**	23, 38, 56, 57
4	2	Duratek High Tech Rubber	450	5-5/8	3-1/8	C47 CS 420PPR^.**	23, 38, 56, 57
4	2	Duratough Polyurethane Polyolefin	700	5-5/8	3-1/8	C47 CS 420PTU^.**	23, 38, 56, 57
4	2	Polyurethane Steel	700	5-5/8	3-1/8	C47 CS 420PU^.**	23, 38, 56, 57
4	2	Semi-Steel	700	5-5/8	3-1/8	C47 CS 420SS^.**	23, 38, 56, 57
4	2	V-Groove	700	5-5/8	3-1/8	C47 CS 420VG^.**	23, 38, 56, 57



Wheel Dia.	Tread Width	Wheel Type	Load Cap.	OAH	Radius	Swivel Part #	^ Bearing Options
4	2	Solid Polyurethane	800	5-5/8	3-1/8	C47CS420SPU^.**	23, 38, 56, 57
4	2	Glass-filled Nylon	800	5-5/8	3-1/8	C47CS420MA^.**	23, 38, 56, 57
4	2	Polyurethane Glass-filled Nylon	800	5-5/8	3-1/8	C47CS420MU^.**	23, 38, 56, 57
4	2	Phenolic	800	5-5/8	3-1/8	C47CS420PH^.**	23, 38, 56, 57
4	2	Sirius HD Donut Polyurethane Aluminum	1000	5-5/8	3-1/8	C47CS420DUA^.**	63
4	2	HD Solid Polyurethane Glass-filled Nylon	1200	5-5/8	3-1/8	C47CS420HU^.**	23, 38, 56, 57, 63
4	2	Ductile Steel	1500	5-5/8	3-1/8	C47CS420DS^.**	23, 38
5	2	Yoke Only	2000	-	-	C47CS520^.**	-
5	2	Elastic Rubber Nylon	450	6-1/2	3-3/4	C47CS520ERN^.**	63
5	2	Duratek High Tech Rubber	500	6-1/2	3-3/4	C47CS520PPR^.**	23, 38, 56, 57
5	2	Duratough Polyurethane Polyolefin	750	6-1/2	3-3/4	C47CS520PTU^.**	23, 38, 56, 57
5	2	Polyurethane Steel	1000	6-1/2	3-3/4	C47CS520PU^.**	23, 38, 56, 57
5	2	Semi-Steel	1000	6-1/2	3-3/4	C47CS520SS^.**	23, 38, 56, 57
5	2	V-Groove	1000	6-1/2	3-3/4	C47CS520VG^.**	23, 38, 56, 57
5	2	Solid Polyurethane	1000	6-1/2	3-3/4	C47CS520SPU^.**	23, 38, 56, 57
5	2	Glass-filled Nylon	1000	6-1/2	3-3/4	C47CS520MA^.**	23, 38, 56, 57
5	2	Polyurethane Glass-filled Nylon	1000	6-1/2	3-3/4	C47CS520MU^.**	23, 38, 56, 57
5	2	Phenolic	1000	6-1/2	3-3/4	C47CS520PH^.**	23, 38, 56, 57
5	2	Sirius HD Donut Polyurethane Aluminum	1200	6-1/2	3-3/4	C47CS520DUA^.**	63
5	2	HD Solid Polyurethane Glass-filled Nylon	1500	6-1/2	3-3/4	C47CS520HU^.**	23, 38, 56, 57, 63
5	2	Ductile Steel	1500	6-1/2	3-3/4	C47CS520DS^.**	23, 38
6	2	Yoke Only	2000	-	-	C47CS620^.**	-
6	2	Elastic Rubber Nylon	550	7-1/2	4-1/2	C47CS620ERN^.**	63
6	2	Duratek High Tech Rubber	600	7-1/2	4-1/2	C47CS620PPR^.**	23, 38, 56, 57
6	2	Duratough Polyurethane Polyolefin	900	7-1/2	4-1/2	C47CS620PTU^.**	23, 38, 56, 57
6	2	Polyurethane Steel	1200	7-1/2	4-1/2	C47CS620PU^.**	23, 38, 56, 57
6	2	Semi-Steel	1200	7-1/2	4-1/2	C47CS620SS^.**	23, 38, 56, 57
6	2	V-Groove	1200	7-1/2	4-1/2	C47CS620VG^.**	23, 38, 56, 57
6	2	Solid Polyurethane	1200	7-1/2	4-1/2	C47CS620SPU^.**	23, 38, 56, 57
6	2	Glass-Filled Nylon	1200	7-1/2	4-1/2	C47CS620MA^.**	23, 38, 56, 57
6	2	Polyurethane Glass-filled Nylon	1200	7-1/2	4-1/2	C47CS620MU^.**	23, 38, 56, 57
6	2	Phenolic	1200	7-1/2	4-1/2	C47CS620PH^.**	23, 38, 56, 57
6	2	Sirius HD Polyurethane Aluminum	1500	7-1/2	4-1/2	C47CS620TUA^.**	63
6	2	Sirius HD Donut Polyurethane Aluminum	1500	7-1/2	4-1/2	C47CS620DUA^.**	63
6	2	HD Solid Polyurethane Glass-filled Nylon	1800	7-1/2	4-1/2	C47CS620HU^.**	23, 38, 56, 57, 63
6	2	Ductile Steel	2000	7-1/2	4-1/2	C47CS620DS^.**	23, 38
8	2	Yoke Only	2000	-	-	C47CS820^.**	-
8	2	Elastic Rubber Nylon	600	9-1/2	6-3/4	C47CS820ERN^.**	63
8	2	Duratek High Tech Rubber	675	9-1/2	6-3/4	C47CS820PPR^.**	23, 38, 56, 57
8	2	Duratough Polyurethane Polyolefin	1000	9-1/2	6-3/4	C47CS820PTU^.**	23, 38, 56, 57
8	2	Polyurethane Steel	1400	9-1/2	6-3/4	C47CS820PU^.**	23, 38, 56, 57
8	2	Semi-Steel	1400	9-1/2	6-3/4	C47CS820SS^.**	23, 38, 56, 57
8	2	V-Groove	1400	9-1/2	6-3/4	C47CS820VG^.**	23, 38, 56, 57
8	2	Solid Polyurethane	1400	9-1/2	6-3/4	C47CS820SPU^.**	23, 38, 56, 57
8	2	Glass-Filled Nylon	1400	9-1/2	6-3/4	C47CS820MA^.**	23, 38, 56, 57
8	2	Polyurethane Glass-filled Nylon	1400	9-1/2	6-3/4	C47CS820MU^.**	23, 38, 56, 57
8	2	Phenolic	1400	9-1/2	6-3/4	C47CS820PH^.**	23, 38, 56, 57
8	2	Sirius HD Polyurethane Aluminum	2000	9-1/2	6-3/4	C47CS820TUA^.**	63, 64
8	2	Sirius HD Donut Polyurethane Aluminum	2000	9-1/2	6-3/4	C47CS820DUA^.**	63, 64
8	2	HD Solid Polyurethane Glass-filled Nylon	2000	9-1/2	6-3/4	C47CS820HU^.**	23, 38, 56, 57, 63
8	2	Ductile Steel	2000	9-1/2	6-3/4	C47CS820DS^.**	23, 38