

## FF | FP | SNP

300 lbs  
135 kg160° F  
-40° F

## FF Flat-Free

300 lbs  
135 kg160° F  
-40° F

## Features

- Quiet, smooth rolling, non-marking
- Maintenance free
- Never flat
- Resists oils, grease, water

## Bearing Options

## Part #

|     |    |
|-----|----|
| 1/2 | 44 |
| 5/8 | 45 |
| 3/4 | 46 |

| Wheel Dia.     | Tread Width | Hub Length | Hub Type | Bearing      | Tread Pattern | Load Cap. | Part #        |
|----------------|-------------|------------|----------|--------------|---------------|-----------|---------------|
| 6              | 2           | 1-3/8*     | 1 pc.    | Flanged Ball | Sawtooth      | 250       | 620FF44L-138F |
| 8 (280/250-4)  | 3           | 3-3/16     | 1 pc.    | Flanged Ball | Sawtooth      | 275       | 830FF44BL-C   |
| 10 (410/350-4) | 3-1/2       | 4          | 1 pc.    | Flanged Ball | Sawtooth      | 300       | 1035FF44BS-C  |
| 10 (410/350-4) | 3-1/2       | 2-1/4*     | 1 pc.    | Flanged Ball | Sawtooth      | 300       | 1035FF45BS-F  |

\* Offset Hub

## FP Pneumatic

300 lbs  
135 kg160° F  
-40° F

## Features

- 4-ply rated tire
- Tube type tire
- Quiet and shock absorbing

## Bearing Options

## Part #

|     |    |
|-----|----|
| 1/2 | 44 |
| 5/8 | 45 |
| 3/4 | 46 |

| Wheel Dia.     | Tread Width | Hub Length | Hub Type | Bearing      | Tread Pattern | Load Cap. | Part #         |
|----------------|-------------|------------|----------|--------------|---------------|-----------|----------------|
| 8 (280/250-4)  | 3           | 3          | 1 pc.    | Flanged Ball | Rib           | 250       | 830FP44B1JT-1C |
| 10 (410/350-4) | 3-1/2       | 4          | 3 pc.    | Flanged Ball | Sawtooth      | 300       | 1035FP44BS-3C  |
| 10 (410/350-4) | 3-1/2       | 2-1/4*     | 3 pc.    | Flanged Ball | Sawtooth      | 300       | 1035FP45BS-F   |

\* Offset Hub

## SNP Semi-Pneumatic on Polyolefin

550 lbs  
250 kg160° F  
-40° F

## Features

- 70 Durometer Shore (A)
- Cushion rubber tread
- Recyclable material, eco friendly
- Flat-free, puncture proof
- Quiet operation, long lasting
- Smooth rolling, quiet

## Bearing Options

## Part #

|                  |    |
|------------------|----|
| 1/2 Flanged Ball | 44 |
| 5/8 Flanged Ball | 45 |
| 3/4 Flanged Ball | 46 |

| Wheel Dia. | Tread Width | Hub Length | **Bearing Options | Tread Pattern | Load Cap. | Part #           |
|------------|-------------|------------|-------------------|---------------|-----------|------------------|
| 10         | 2-3/4       | 2-1/4*     | 44, 45, 46        | Rib           | 550       | 10275SNP**AR-F-R |

\* Off-Centered