


PH



PH Phenolic



Features

- 90 (±5) Durometer Shore (D)
- Use metal only bearing components for temperatures over 180°
- Resistant to high shock, impact, oils and grease
- Economic wheel made in the USA
- NOT recommended for wet applications
- Zerk fittings available in 5, 6, 8 x 2 as well as all 2-1/2 & 3 wide wheels

Bearing Options	Part #
1/2 Roller	21
3/4 Roller	23
1 Roller	25
1-1/4 Roller	26
1/2 Q34 Precision Ball	38

Bearing Options	Part #
3/4 Double Groove Precision	39D
1 Double Groove Precision	40D
1/2 Delrin	56
3/4 Delrin	57

Wheel Dia.	Tread Width	Hub Length	Load Cap.	Plain Bore Dia.	Part #	*Plain Bore	*Roller	*Delrin	*Precision Ball
3	1-1/4	1-3/8	400	1/2, 1-1/16	314PH*	83	21	56	-
3-1/4	2	2-3/16	700	1-3/16	3420PH*	84	23	56, 57	38
3-1/2	1-1/4	1-3/8	400	1-1/16	3514PH*	83	21	56	-
4	1-1/4	1-3/8	400	1/2, 1-1/16	414PH*	83	21	56	-
4	1-1/2	1-5/8	600	1-3/16	415PH*	84	23	56, 57	38
4	2	2-3/16	800	1-3/16	420PH*	84	23	56, 57	38
5	1-1/4	1-3/8	400	1/2, 1-1/16	514PH*	83	21	56	-
5	1-1/2	1-5/8	600	1-3/16	515PH*	84	23	56, 57	38
5	2	2-3/16	1000	1-3/16	520PH*	84	23	56, 57	38
6	1-1/2	1-5/8	800	1-3/16	615PH*	84	23	56, 57	38
6	2	2-3/16	1200	1-3/16	620PH*	84	23	56, 57	38
6	2-1/2	2-3/4	1600	1-15/16	625PH*	86	25, 26	-	-
6	3	3-1/4	2000	1-15/16	630PH*	86	25, 26	-	39D, 40D
8	2	2-3/16	1400	1-3/16	820PH*	84	23	56, 57	38
8	2-1/2	2-3/4	2000	1-15/16	825PH*	86	25, 26	-	-
8	3	3-1/4	2500	1-15/16	830PH*	86	25, 26	-	39D, 40D
10	2-1/2	2-3/4	2500	1-3/16, 1-15/16	1025PH*	84, 86	23, 25, 26	-	-
10	3	3-1/4	2900	1-15/16	1030PH*	86	25, 26	-	39D, 40D
12	2-1/2	2-3/4	3000	1-15/16	1225PH*	86	25, 26	-	-
12	3	3-1/4	3500	1-15/16	1230PH*	86	25, 26	-	39D, 40D