

PPR | DTR



675 lbs  
305 kg



180° F  
-45° F



PPR | DTR Duratek High Tech Rubber



675 lbs  
305 kg



180° F  
-45° F



Features

- 65 Durometer Shore (A)
- High-grade thermoplastic elastomer mechanically bonded to polyolefin core
- Resists most solvents, oil, grease and water
- Non-marking, quiet and smooth operation
- Great for factory, institutional and food service environments

Bearing Options	Part #
3/8 Annular	11
3/4 Roller	23
1/2 Q34 Precision Ball	38
1/2 Delrin	56
3/4 Delrin	57

Wheel Dia.	Tread Width	Hub Length	Load Cap.	Plain Bore Dia.	Flat Tread #	Donut Tread #	*Plain Bore	*Roller	*Precision Ball	*Annular Ball	*Delrin
2-1/2	1-1/4	1-9/16	150	-	2514PPR35X	--	-	-	35	-	-
3	1-1/4	1-1/2	225	7/8	314PPR*	--	89	-	-	11	56
3-1/2	1-1/4	1-1/2	250	7/8	3514PPR*	--	89	-	-	11	56
4	1-1/4	1-1/2	300	7/8	414PPR*	--	89	-	-	11	56
4	1-1/2	1-5/8	400	1-3/16	415PPR*	--	84	23	38	-	56, 57
4	2	2-3/16	450	1-3/16	420PPR*	420DTR*	84	23	38	-	56, 57
5	1-1/4	1-1/2	325	7/8	514PPR*	--	89	-	-	11	56
5	1-1/2	1-5/8	450	1-3/16	515PPR*	--	84	23	38	-	56, 57
5	2	2-3/16	500	1-3/16	520PPR*	520DTR*	84	23	38	-	56, 57
6	1-1/2	1-5/8	500	1-3/16	615PPR*	--	84	23	38	-	56, 57
6	2	2-3/16	600	1-3/16	620PPR*	620DTR*	84	23	38	-	56, 57
8	2	2-3/16	675	1-3/16	820PPR*	820DTR*	84	23	38	-	56, 57