




PPU Polyurethane on Polyolefin



Features

- Injection Molded Polyurethane
- 90-95 Durometer Shore (A) Polyurethane Tread chemically bonded to polyolefin core
- High capacity and lightweight
- Resists oil, grease, water and most solvents
- Non-marking, smooth rolling and quiet
- Various colors available

Wheel Dia.	Tread Width	Hub Length	Load Cap.	Part #	*Plain Bore	*Roller	*Precision Ball	*Flanged Ball	Delrin
2	7/8	1	100	278PPU*	80	-	-	-	-
2-1/2	7/8	1	100	2578PPU*	80	-	-	-	-
3	7/8	1	100	378PPU*	80	-	-	-	-
3	1-1/4	1-9/16	250	314PPU*	-	-	34	-	-
3-1/2	1-1/4	1-9/16	275	3514PPU*	-	-	34	-	-
4	1-1/4	1-9/16	300	414PPU*	-	-	31, 34	-	-
4	2	2-3/16	500	420PPU*	84	23	38	-	56, 57
5	1	1-1/8	145	510PPU*	81	-	-	-	-
5	1-1/4	1-9/16	325	514PPU*	-	-	31, 34	41, 42	-
5	2	2-3/16	600	520PPU*	84	23	38	-	56, 57
6	1-1/4	1-9/16	350	614PPU*	-	-	34, 35	42	-
6	2	2-3/16	720	620PPU*	84	23	38	-	56, 57
8	1-1/2	2	600	815PPU*	-	-	-	44,45, 46	-
8	2	2-3/16	800	820PPU*	84	23	38	-	56, 57
10	1-1/2	2	700	1015PPU*	-	-	-	44,45, 46	-
10	2-1/2	2-3/4	1400	1025PPU*	86	25	-	-	-



Plain Bore Diameter	Part #
1/4 Plain Bore	80
5/16 Plain Bore	81
1-3/16 Plain Bore	84
1-15/16 Plain Bore	86

Bearing Options	Part #
3/4 Roller	23
1 Roller	25
5/16 Precision Thread Guard	31
3/8 Precision Full Thread Guard	34
3/8 Precision Small Thread Guard	35
1/2 Q34 Precision Ball	38
5/16 Flanged Ball	41
3/8 Flanged Ball	42
1/2 Flanged Ball	44
5/8 Flanged Ball	45
3/4 Flanged Ball	46
1/2 Delrin	56
3/4 Delrin	57