

PTU | DTU



PTU | DTU DURATOUGH Hi-Tech Polyurethane on Polyolefin



Features

- Liquid cast flow through 100% polyurethane tread
- 90-95 Durometer Shore (A) polyurethane tread mechanically bonded to polyolefin core
- High capacity and lightweight
- Resists oil, grease, water, and most solvents
- Non-marking, smooth rolling and quiet
- Multi-year tread durability
- Various colors available

Wheel Dia.	Tread Width	Hub Length	Load Cap.	Flat Tread #	Donut Tread #	*Plain Bore	*Roller	*Precision Ball	*Annular Ball	Delrin
3	1-1/4	1-9/16	275	314PTU*	--	89	-	-	11	56
3-1/2	1-1/4	1-9/16	300	3514PTU*	--	89	-	-	11	56
4	1-1/4	1-9/16	325	414PTU*	--	89	-	-	11	56
4	2	2-3/16	700	420PTU*	420DTU*	84	23	38	-	56, 57
5	1-1/4	1-9/16	350	514PTU*	--	89	-	-	11	56
5	2	2-3/16	750	520PTU*	520DTU*	84	23	38	-	56, 57
6	2	2-3/16	900	620PTU*	620DTU*	84	23	38	-	56, 57
6	3	3-1/4	1400	630PTU*	--	86	25, 26	39D	-	-
8	2	2-3/16	1000	820PTU*	820DTU*	84	23	38	-	56, 57
8	3	3-1/4	1500	830PTU*	--	86	25, 26	39D	-	-
10	3	3-1/4	1650	1030PTU*	--	86	25, 26	39D	-	-
12	3	3-1/4	1800	1230PTU*	--	86	25, 26	39D	-	-

Plain Bore Diameter	Part #
1-3/16 Plain Bore	84
1-15/16 Plain Bore	86
7/8 Plain Bore	89

Bearing Options	Part #
3/4 Roller	23
1 Roller	25
1-1/4 Roller	26
1/2 Q34 Precision Ball	38
3/4 Double Groove Precision	39D
1/2 Delrin	56
3/4 Delrin	57

Suffix Color Code:

X

G

J

U

A

