



PU Polyurethane on Steel



Features

- 90-95 Durometer Shore (A)
- 10 mm thick polyurethane tread
- Chemically bonded to heavy steel core
- Non-marking, non-staining, non-conductive tread
- Resists oil, grease, water and solvents
- Zerk fitting

Bearing Options	Part #
3/4 Roller	23
1 Roller	25
1-1/4 Roller	26
1/2 Q34 Precision Ball	38
3/4 Double Groove Precision	39D
1 Double Groove Precision	40D

Wheel Dia.	Tread Width	Hub Length	Load Cap.	Plain Bore Dia.	Part #	*Plain Bore	*Roller	*Precision Ball
3-1/4	2	2-3/16	600	1-3/16	3420PU*	84	23	38
4	1-1/2	2-3/16	600	1-3/16	415PU*	84	23	38
4	2	2-3/16	700	1-3/16	420PU*	84	23	38
5	1-1/2	2-3/16	700	1-3/16	515PU*	84	23	38
5	2	2-3/16	1000	1-3/16	520PU*	84	23	38
6	2	2-3/16	1200	1-3/16	620PU*	84	23	38
6	2-1/2	2-3/4	1600	1-15/16	625PU*	86	25, 26	-
6	3	3-1/4	2000	1-15/16	630PU*	86	25, 26	39D, 40D
8	2	2-3/16	1400	1-3/16	820PU*	84	23	38
8	2-1/2	2-3/4	2000	1-15/16	825PU*	86	25, 26	-
8	3	3-1/4	2500	1-15/16	830PU*	86	25, 26	39D, 40D
10	2-1/2	2-3/4	2200	1-15/16	1025PU*	86	25, 26	-
10	3	3-1/4	3000	1-15/16	1030PU*	86	25, 26	39D, 40D
12	2-1/2	2-3/4	2500	1-15/16	1225PU*	86	25, 26	-
12	3	3-1/4	3500	1-15/16	1230PU*	86	25, 26	39D, 40D