

RS



2100 lbs  
950 kg



160° F  
-40° F



RS Rubber on Steel



2100 lbs  
950 kg



160° F  
-40° F

Features

- 70 Durometer Shore (A)
- Cushion rubber tread vulcanized to steel center
- Excellent floor and load protection
- Easy rolling, shock absorption and quiet operation
- Zerk fitting

Bearing Options	Part #
3/4 Roller	23
1 Roller	25
1/2 Q34 Precision Ball	38
3/4 Double Groove Precision	39D

Wheel Dia.	Tread Width	Hub Length	Load Cap.	Plain Bore Dia.	Part #	**Plain Bore	**Roller	** Precision Ball
4	2	2-3/16	400	1-3/16	420RS**B	84	23	38
5	2	2-3/16	450	1-3/16	520RS**B	84	23	38
6	2	2-3/16	550	1-3/16	620RS**B	84	23	38
6	2-1/2	2-3/4	700	1-15/16	625RS**B	86	25	-
6	3	3-1/4	750	1-15/16	630RS**B	86	25	39D
8	2	2-3/16	600	1-3/16	820RS**B	84	23	38
8	2-1/2	2-3/4	850	1-3/16, 1-15/16	825RS**B	84, 86	23, 25	-
8	3	3-1/4	900	1-15/16	830RS**B	86	25	39D
10	2	2-3/16	720	1-3/16	1020RS**B	84	23	38
10	2-1/2	2-3/4	1000	1-3/16, 1-15/16	1025RS**B	84, 86	23, 25	-
10	3	3-1/4	1100	1-15/16	1030RS**B	86	25	39D
12	2-1/2	2-3/4	1200	1-15/16	1225RS**B	86	25	-
12	3	3-1/4	1300	1-15/16	1230RS**B	86	25	39D
12	5	5-1/4	2100	2-7/16	1250RS**B	87	-	-