



SPU Solid Polyurethane



Features

- 63 (±5) Durometer Shore (D)
- 100% washable
- One piece mold design eliminates bonding failure
- High impact and abrasion resistant
- Resists oil, grease, water and most solvents
- Perfect for food processing equipment and other stainless applications

Bearing Options	Part #
3/4 Roller	23
1/2 Q34 Precision Ball	38
1/2 Delrin	56
3/4 Delrin	57
1/2 Plain Bore	83
1-3/16 Plain Bore	84

Wheel Dia.	Tread Width	Hub Length	Load Cap.	Plain Bore Dia.	Part #	*Plain Bore	*Roller	*Precision Ball	*Delrin
3	1-1/4	1-9/16	300	1/2	314SPU*	83	-	-	-
4	1-1/4	1-9/16	400	1/2	414SPU*	83	-	-	-
4	2	2-3/16	800	1-3/16	420SPU*	84	23	38	56, 57
5	1-1/4	1-9/16	700	1/2	514SPU*	83	-	-	-
5	2	2-3/16	1000	1-3/16	520SPU*	84	23	38	56, 57
6	2	2-3/16	1200	1-3/16	620SPU*	84	23	38	56, 57
8	2	2-3/16	1400	1-3/16	820SPU*	84	23	38	56, 57