



TPH Hi-Temp Phenolic



Features

- 90 (±5) Durometer Shore (D)
- Use metal only bearing components for temperatures over 180°
- Resistant to high shock, impact, oils and grease
- Economic wheel made in the USA
- NOT recommended for wet applications
- +475°F continuous heat resistance
- +550°F (intermittent) heat resistance
- Zerk fittings in 5x2, 6x2, 8x2, and all 2-1/2 & 3 wide wheels are available

Wheel Dia.	Tread Width	Hub Length	Load Cap.	Plain Bore Dia.	Part #	*Plain Bore	*Roller
3	1-1/4	1-3/8	200	1-1/16	314TPH*	83	-
4	1-1/4	1-3/8	250	1-1/16	414TPH*	83	-
4	2	2-3/16	600	1-3/16	420TPH*	84	23
5	1-1/4	1-3/8	300	1-1/16	514TPH*	83	-
5	2	2-3/16	750	1-3/16	520TPH*	84	23
6	2	2-3/16	900	1-3/16	620TPH*	84	23
6	3	3-1/4	1700	1-15/16	630TPH*	86	25, 26
8	2	2-3/16	1100	1-3/16	820TPH*	84	23
8	3	3-1/4	1900	1-15/16	830TPH*	86	25, 26
10	3	3-1/4	2400	1-15/16	1030TPH*	86	25, 26
12	3	3-1/4	2600	1-15/16	1230TPH*	86	25, 26

Bearing Options	Part #
3/4 Roller	23
1 Roller	25
1-1/4 Roller	26